



2.4Ghz Wireless USB cable IP camera

Selling Points:

1. Wireless hidden IP camera is more convenient and safe than the traditional big & showy one.
2. Unique design and clever covered camera(it's just a normal cable).
3. Very clear video with high definition up to 786X576 pix, 520TVL.
4. Work day & night: Excellent night vision with low illumination to 0.008lux.
5. Strong output power brings long transmission range up to 150m(L.O.S.)
6. Encrypted frequency(2.3G) available to avoid interference from Wifi equipments,WLAN network, bluetooth equipments;and other general 2.4GHz equipments can't receive your signal,protect privacy well.
7. Best choice for remote & continuous surveillance of home,offices,shops,pubs and restaurants, buildings, warehouses,etc

Specification:

1) Wireless USB Cable Camera

Channels	2.4G	2414Mhz(CH1) 2432MHz (CH2) 2450MHz (CH3) 2468MHz (CH4)		Working channel: any 1 of 8 (factory default: 2414Mhz-CH1)
	2.3G	2370Mhz(CH1) 2390MHz (CH2) 2490MHz (CH3) 2510MHz (CH4)		
Audio subcarrier frequency	6.0Mhz			
Antenna	Built-in 2.4G antenna			
RF output power	100mW			
Transmission Range	150m			
CMOS Total Pixels	NTSC : 656 (H) ×492 (V)		PAL : 786 (H) ×576 (V)	
Horizontal resolution	520TV Lines			
Minimum Illumination	0.008Lux/F1.2			
Lens size view angle	0.5mm F2.0 / 55 °			
S/N RATIO	> 48dB			
Size (L)	1.8 meters { lens size (L x D) : 35mm X 15mm }			
Net weight	45g			
Current	160mA			
Voltage	DC 3.3V-6V			
Operating Temperature	- 20°C ~ + 50°C , relative humidity 85%			

2) Wireless Network Video Server



Frontview



Backview

2.4GHz Wireless Receiving	
Receiving Frequency	ISM 2,360MHz~2,520MHz
Audio subcarrier frequency	Default: 6.0Mhz Optional:6.5MHz
Channel	Support 8 channels
Receiving Sensitivity	≤ -85dBm
Antenna	50ohm SMA
AV INPUT	
Video Input Level	1Vp-p@75ohm
Audio Input Level	1Vp-p@1Kohm
Power Supply output	DC5V
Compression standard	
Video frequency compression standard	H.264/MJPEG
Compression output code rate	32K~4Mbps/1M~16Mbps
Audio frequency compression standard	G.711
Audio frequency output code rate	64Kbps
Image	
Image size	704*576; 704*288; 352*288; 176*144704*480;
Frame Rate	1-30f/s
Function	
2.4GHz wireless receiving	Support
AV input of wired camera	Support
Mobile phone monitoring	Support
Network protocol	PPPoE, DHCP, TCP/IP, HTTP, UDP, RTP/RTCP
Motion detection	Support
Area shield	Support
SD Card local storage	Support
If order wifi function, the wireless camera must be 2.3Ghz	Support encryption: wep64,wep128,wpa,wpa2
	Wireless power: 13dbm(54M) (high power module, wireless power: 20dbm/54M)
	Wireless distance: <=70m (high power module<=300M)
General specifications	
Working temperature	-10℃~65℃
Working humidity	85%RH or less
Power source	DC5V/1A
Power consumption	<3W
Size (LXWXH)	7.5cm x 10.5cm x 2.9cm
Weight	180g